

56S 丸棒

JIS 規格 H4040 A5056B

特性の概要 耐食性、切削加工性が良い。アルミ合金丸棒の代表商品。

用 途 光学機器、通信機器部品、ファスナー 等

◎当社在庫品 ○取寄せ品

径	m/kg		径	m/kg		径	m/kg		径	m/kg	
5	0.05	○	34	2.41	◎	63	8.26	○	210	91.79	○
6	0.07	○	35	2.55	◎	64	8.53	○	220	100.74	◎
7	0.10	○	36	2.70	◎	65	8.79	◎	230	110.10	◎
8	0.13	○	37	2.85	○	70	10.20	◎	240	119.88	◎
9	0.17	○	38	3.01	◎	75	11.71	◎	250	130.08	◎
10	0.21	○	39	3.17	○	80	13.32	◎	260	140.70	○
11	0.25	○	40	3.33	◎	85	15.04	◎	270	151.73	○
12	0.30	○	41	3.50	○	90	16.86	◎	280	163.17	○
13	0.35	○	42	3.67	◎	95	18.78	◎	290	175.04	○
14	0.41	○	43	3.85	○	100	20.81	◎	300	187.32	○
15	0.47	○	44	4.03	○	105	22.95	◎	310	200.01	○
16	0.53	◎	45	4.21	◎	110	25.18	◎	320	213.13	○
17	0.60	○	46	4.40	◎	115	27.53	◎	330	226.65	○
18	0.67	◎	47	4.60	○	120	29.97	◎	340	240.60	○
19	0.75	○	48	4.80	○	125	32.52	◎	350	254.96	○
20	0.83	◎	49	5.00	○	130	35.17	◎	360	269.74	○
21	0.92	○	50	5.20	◎	135	37.93	◎	370	284.93	○
22	1.01	○	51	5.41	○	140	40.79	◎	375	292.68	○
23	1.10	○	52	5.63	○	145	43.76	○	380	300.54	○
24	1.20	○	53	5.85	○	150	46.83	◎	390	316.57	○
25	1.30	◎	54	6.07	○	155	50.00	○	400	333.01	○
26	1.41	○	55	6.30	◎	160	53.28	○	420	367.14	○
27	1.52	○	56	6.53	○	165	56.66	○	450	421.47	○
28	1.63	◎	57	6.76	○	170	60.15	◎			
29	1.75	○	58	7.00	○	175	63.74	○			
30	1.87	◎	59	7.25	○	180	67.43	◎			
31	2.00	○	60	7.49	◎	185	71.23	○			
32	2.13	◎	61	7.74	○	190	75.14	◎			
33	2.27	○	62	8.00	○	200	83.25	◎			

※ 重量参考 値

*在庫状況・切断等につきましてはお問合せ下さい。