

# 17S 丸棒

JIS 規格 H4040 A2017B

**特性の概要** 耐食性、溶接性は劣るが、強度が高く切削加工性が良い。

**用 途** 加工度の高い一般部品、航空機用材、自動車用部材 等

◎当社在庫品 ○取寄せ品

径	m/kg		径	m/kg		径	m/kg		径	m/kg	
5	0.05	○	34	2.54	◎	63	8.73	○	200	87.96	◎
6	0.08	○	35	2.69	◎	64	9.01	○	210	96.98	○
7	0.11	○	36	2.85	◎	65	9.29	◎	220	106.44	○
8	0.14	○	37	3.01	○	70	10.78	◎	230	116.33	○
9	0.18	○	38	3.18	◎	71	11.09	○	240	126.67	○
10	0.22	◎	39	3.34	○	75	12.37	◎	250	137.45	○
11	0.27	○	40	3.52	◎	80	14.07	◎	260	148.66	○
12	0.32	○	41	3.70	○	81	14.43	○	270	160.32	○
13	0.37	○	42	3.88	◎	85	15.89	◎	280	172.41	○
14	0.43	○	43	4.07	○	90	17.81	◎	290	184.95	○
15	0.49	○	44	4.26	○	95	19.85	◎	300	197.92	○
16	0.56	○	45	4.45	◎	100	21.99	◎	350	269.39	○
17	0.64	○	46	4.65	○	105	24.25	◎	400	351.86	○
18	0.71	○	47	4.86	○	110	26.61	◎			
19	0.79	○	48	5.07	○	115	29.08	○			
20	0.88	◎	49	5.28	○	120	31.67	◎			
21	0.97	○	50	5.50	◎	125	34.36	◎			
22	1.06	◎	51	5.72	○	130	37.17	◎			
23	1.16	○	52	5.95	○	135	40.08	◎			
24	1.27	○	53	6.18	○	140	43.10	◎			
25	1.37	◎	54	6.41	○	145	46.24	○			
26	1.49	○	55	6.65	◎	150	49.48	◎			
27	1.60	○	56	6.90	○	155	52.83	○			
28	1.72	○	57	7.14	○	160	56.30	◎			
29	1.85	○	58	7.40	○	165	59.87	○			
30	1.98	◎	59	7.66	○	170	63.55	◎			
31	2.11	○	60	7.92	◎	175	67.35	○			
32	2.25	◎	61	8.18	○	180	71.25	◎			
33	2.39	○	62	8.45	○	190	79.39	◎			

※ 重量参考 値

\*在庫状況・切断等につきましてはお問合せ下さい。