

63S 平角管

JIS 規格 H4100 A6063

旧呼称 63S

特性の概要 6061 より強度は低いが、耐食性、表面処理製に優れる。

用 途 アルミサッシ、熱交換器部品、形状の複雑な量産部品 等

寸 法	m/kg	4m	5m	寸 法	m/kg	4m	5m
10 × 15 × 1.2	0.146		○	50 × 100 × 2.5	1.960	○	○
12 × 25 × 1.2	0.230		○	50 × 100 × 3.0	2.340		○
15 × 25 × 1.5	0.302	○	○	50 × 150 × 2.5	2.640		○
15 × 30 × 1.5	0.340		○	50 × 150 × 3.0	3.150		○
20 × 30 × 1.5	0.380		○	60 × 120 × 2.5	2.370		○
20 × 30 × 2.0	0.500	○	○				
20 × 30 × 2.5	0.610		○				
20 × 40 × 2.0	0.609	○	○				
20 × 40 × 2.5	0.750		○				
25 × 30 × 3.0	0.800		○				
25 × 40 × 3.0	0.960		○				
25 × 50 × 2.0	0.772	○	○				
25 × 60 × 2.0	0.881	○	○				
30 × 40 × 2.0	0.718	○	○				
30 × 50 × 2.0	0.820		○				
30 × 60 × 2.0	0.936	○	○				
30 × 60 × 2.5	1.150		○				
30 × 70 × 2.0	1.040		○				
30 × 70 × 2.4	1.240		○				
30 × 70 × 3.0	1.534	○	○				
30 × 100 × 2.0	1.370		○				
30 × 100 × 2.5	1.690		○				
40 × 60 × 2.0	1.044		○				
40 × 60 × 2.5	1.290		○				
40 × 60 × 3.0	1.534	○	○				
40 × 60 × 4.0	1.990		○				
40 × 70 × 3.0	1.690		○				
40 × 80 × 2.5	1.564	○	○				
40 × 80 × 3.0	1.850		○				

※ 重量参考 値

*在庫状況・切断等につきましてはお問合せ下さい。