

## 銅丸管(りん脱酸銅丸管)

JIS 規格 H3300 C1220T H

旧 呼 称 DCuT

**特性の概要** 水素ゼイ化を起こさない。押広げ性、曲げ性、絞り性に優れている。

**用 途** 熱交換器用、化学工業用、給水・給湯用、ガス管 等

定尺:5000

寸 法	P/kg		寸 法	P/kg		寸 法	P/kg	
3.0 × 0.5	0.18	○	8.0 × 1.2	1.15	○	12.0 × 3.0	3.82	○
3.0 × 0.8	0.25	○	8.0 × 1.5	1.38	○	12.7 × 0.8	1.35	○
3.2 × 0.5	0.19	○	8.0 × 2.0	1.70	○	12.7 × 1.0	1.65	○
3.5 × 0.5	0.21	○	9.0 × 0.8	0.93	○	12.7 × 1.2	1.95	○
4.0 × 0.5	0.25	○	9.0 × 1.0	1.13	○	12.7 × 1.5	2.38	○
4.0 × 0.8	0.36	○	9.0 × 1.5	1.59	○	12.7 × 2.0	3.03	○
4.0 × 1.0	0.42	○	9.5 × 0.5	0.64	○	12.7 × 3.0	4.11	○
4.5 × 0.5	0.28	○	9.5 × 0.8	0.98	○	14.0 × 1.0	1.84	○
4.8 × 0.8	0.45	○	9.5 × 1.0	1.20	○	14.0 × 1.2	2.17	○
5.0 × 0.5	0.32	○	9.5 × 1.2	1.41	○	14.0 × 1.5	2.65	○
5.0 × 0.8	0.48	○	9.5 × 1.5	1.70	○	14.0 × 2.0	3.39	○
5.0 × 1.0	0.57	○	9.5 × 2.0	2.12	○	14.0 × 3.0	4.67	○
6.0 × 0.5	0.39	○	10.0 × 0.5	0.67	○	15.0 × 1.0	1.98	○
6.0 × 0.8	0.59	○	10.0 × 0.8	1.04	○	15.0 × 1.2	2.34	○
6.0 × 1.0	0.71	○	10.0 × 1.0	1.27	○	15.0 × 1.5	2.86	○
6.0 × 1.2	0.81	○	10.0 × 1.2	1.49	○	15.0 × 1.8	3.36	○
6.0 × 1.5	0.95	○	10.0 × 1.5	1.80	○	15.0 × 2.0	3.68	○
6.0 × 2.0	1.13	○	10.0 × 1.8	2.09	○	15.0 × 2.3	4.13	○
6.35 × 0.5	0.41	○	10.0 × 2.0	2.26	○	15.0 × 3.0	5.09	○
6.35 × 0.8	0.63	○	10.0 × 2.6	2.72	○	15.9 × 0.8	1.71	○
6.35 × 1.0	0.76	○	11.0 × 1.0	1.41	○	15.9 × 1.0	2.11	○
6.35 × 1.2	0.87	○	11.0 × 1.5	2.01	○	15.9 × 1.2	2.49	○
6.35 × 1.5	1.03	○	11.0 × 2.0	2.54	○	15.9 × 1.5	3.05	○
6.35 × 2.0	1.23	○	12.0 × 0.8	1.27	○	15.9 × 2.0	3.93	○
7.0 × 1.0	0.85	○	12.0 × 1.0	1.56	○	15.9 × 2.5	4.74	○
7.0 × 1.5	1.17	○	12.0 × 1.2	1.83	○	15.9 × 3.0	5.47	○
8.0 × 0.5	0.53	○	12.0 × 1.5	2.23	○	16.0 × 2.0	3.96	○
8.0 × 0.8	0.81	○	12.0 × 1.8	2.60	○	16.0 × 2.5	4.77	○
8.0 × 1.0	0.99	○	12.0 × 2.0	2.83	○	16.0 × 3.0	5.51	○

※ 重量参考 値

\*在庫状況・切断等につきましてはお問合せ下さい。

## 銅丸管(りん脱酸銅丸管)

定尺:5000

寸 法	P/kg		寸 法	P/kg		寸 法	P/kg	
16.0 × 4.0	6.79	○	22.0 × 3.0	8.06	○	28.0 × 2.0	7.35	○
17.0 × 2.0	4.24	○	22.0 × 3.5	9.15	○	28.0 × 2.5	9.01	○
18.0 × 1.0	2.40	○	22.0 × 4.0	10.18	○	28.0 × 3.0	10.60	○
18.0 × 1.2	2.85	○	22.0 × 5.0	12.02	○	28.5 × 1.0	3.89	○
18.0 × 1.5	3.50	○	22.2 × 0.8	2.42	○	28.5 × 1.2	4.63	○
18.0 × 2.0	4.52	○	22.2 × 1.0	3.00	○	28.5 × 1.5	5.73	○
18.0 × 3.0	6.36	○	22.2 × 1.2	3.56	○	28.5 × 2.0	7.49	○
19.0 × 0.8	2.06	○	22.2 × 1.5	4.39	○	28.5 × 3.0	10.81	○
19.0 × 1.0	2.54	○	24.0 × 2.0	6.22	○	30.0 × 1.0	4.10	○
19.0 × 1.2	3.02	○	25.0 × 1.0	3.39	○	30.0 × 1.5	6.04	○
19.0 × 1.5	3.71	○	25.0 × 1.2	4.04	○	30.0 × 2.0	7.92	○
19.0 × 2.0	4.81	○	25.0 × 1.5	4.98	○	30.0 × 2.5	9.72	○
19.0 × 2.5	5.83	○	25.0 × 1.8	5.90	○	30.0 × 3.0	11.45	○
19.0 × 3.0	6.79	○	25.0 × 2.0	6.50	○	30.0 × 4.0	14.70	○
19.0 × 4.0	8.48	○	25.0 × 2.5	7.95	○	30.0 × 5.0	17.67	○
19.0 × 5.0	9.90	○	25.0 × 3.0	9.33	○	31.8 × 0.8	3.51	○
20.0 × 1.0	2.69	○	25.0 × 4.0	11.88	○	31.8 × 1.0	4.35	○
20.0 × 1.2	3.19	○	25.0 × 5.0	14.14	○	31.8 × 1.2	5.19	○
20.0 × 1.5	3.92	○	25.4 × 0.8	2.78	○	31.8 × 1.5	6.43	○
20.0 × 1.8	4.63	○	25.4 × 1.0	3.45	○	31.8 × 2.0	8.43	○
20.0 × 2.0	5.09	○	25.4 × 1.2	4.11	○	31.8 × 2.5	10.36	○
20.0 × 2.5	6.19	○	25.4 × 1.5	5.07	○	31.8 × 3.0	12.21	○
20.0 × 3.0	7.21	○	25.4 × 2.0	6.62	○	31.8 × 3.5	14.00	○
20.0 × 4.0	9.05	○	25.4 × 2.5	8.09	○	31.8 × 4.0	15.72	○
20.0 × 5.0	10.60	○	25.4 × 3.0	9.50	○	31.8 × 5.0	18.94	○
22.0 × 1.0	2.97	○	25.4 × 5.0	14.42	○	34.0 × 2.0	9.05	○
22.0 × 1.5	4.35	○	27.0 × 3.0	10.18	○	34.0 × 3.0	13.15	○
22.0 × 2.0	5.65	○	28.0 × 1.0	3.82	○	35.0 × 1.0	4.81	○
22.0 × 2.5	6.89	○	28.0 × 1.5	5.62	○	35.0 × 1.2	5.73	○

※ 重量参考 値

\*在庫状況・切断等につきましてはお問合せ下さい。

## 銅丸管(りん脱酸銅丸管)

定尺:5000

寸 法	P/kg		寸 法	P/kg		寸 法	P/kg	
35.0 × 1.5	7.10	○	44.5 × 1.0	6.15	○	54.0 × 2.0	14.70	○
35.0 × 2.0	9.33	○	44.5 × 1.2	7.35	○	55.0 × 2.0	14.99	○
35.0 × 2.5	11.49	○	44.5 × 1.5	9.12	○	55.0 × 2.5	18.56	○
35.0 × 3.0	13.57	○	44.5 × 2.0	12.02	○	55.0 × 3.0	22.05	○
35.0 × 3.5	15.59	○	44.5 × 2.5	14.84	○	55.0 × 5.0	35.34	○
35.0 × 4.0	17.53	○	44.5 × 3.0	17.60	○	57.0 × 1.2	9.47	○
35.0 × 5.0	21.21	○	44.5 × 5.0	27.92	○	57.0 × 1.5	11.77	○
38.0 × 0.8	4.21	○	45.0 × 2.0	12.16	○	57.0 × 3.0	22.90	○
38.0 × 1.0	5.23	○	45.0 × 2.5	15.02	○	58.0 × 2.0	15.83	○
38.0 × 1.2	6.24	○	45.0 × 4.0	23.19	○	60.0 × 1.5	12.41	○
38.0 × 1.5	7.74	○	45.0 × 5.0	28.27	○	60.0 × 2.0	16.40	○
38.0 × 2.0	10.18	○	48.0 × 3.0	19.09	○	60.0 × 3.0	24.17	○
38.0 × 2.5	12.55	○	48.6 × 3.0	19.34	○	60.0 × 5.0	38.88	○
38.0 × 3.0	14.84	○	50.0 × 1.5	10.28	○	60.0 × 6.0	45.80	○
38.0 × 3.5	17.07	○	50.0 × 2.0	13.57	○	63.5 × 1.5	13.15	○
38.0 × 4.0	19.23	○	50.0 × 3.0	19.93	○	63.5 × 2.0	17.39	○
38.0 × 5.0	23.33	○	50.0 × 4.0	26.01	○	63.5 × 2.5	21.56	○
40.0 × 1.5	8.16	○	50.0 × 5.0	31.81	○	63.5 × 3.0	25.66	○
40.0 × 2.0	10.74	○	50.8 × 1.2	8.41	○	63.5 × 4.0	33.65	○
40.0 × 2.5	13.25	○	50.8 × 1.5	10.45	○	63.5 × 5.0	41.35	○
40.0 × 3.0	15.69	○	50.8 × 1.8	12.47	○	65.0 × 3.0	26.30	○
40.0 × 3.5	18.06	○	50.8 × 2.0	13.80	○	66.8 × 1.5	13.85	○
40.0 × 4.0	20.36	○	50.8 × 2.5	17.07	○	66.8 × 2.0	18.32	○
40.0 × 5.0	24.74	○	50.8 × 3.0	20.27	○	67.5 × 1.5	14.00	○
41.3 × 1.2	6.80	○	50.8 × 4.0	26.46	○	70.0 × 2.0	19.23	○
41.3 × 1.5	8.44	○	50.8 × 5.0	32.37	○	70.0 × 3.0	28.42	○
41.3 × 2.0	11.11	○	50.8 × 6.0	38.00	○	70.0 × 5.0	45.95	○
41.3 × 3.0	16.24	○	53.0 × 5.0	33.93	○	76.2 × 1.5	15.84	○
42.7 × 3.0	16.84	○	54.0 × 1.5	11.13	○	76.2 × 2.0	20.98	○

※ 重量参考 値

\*在庫状況・切断等につきましてはお問合せ下さい。

## 銅丸管(りん脱酸銅丸管)

定尺:5000

寸 法	P/kg	
76.2 × 2.5	26.05	○
76.2 × 3.0	31.05	○
76.2 × 4.0	40.83	○
76.2 × 5.0	50.33	○
80.0 × 1.5	16.65	○
80.0 × 3.0	32.66	○
80.0 × 4.0	42.98	○
80.0 × 5.0	53.01	○
82.5 × 3.0	33.72	○
82.5 × 5.0	54.78	○
89.0 × 2.0	24.60	○
89.0 × 3.0	36.47	○
89.0 × 5.0	59.38	○
101.6 × 2.0	28.16	○
101.6 × 3.0	41.82	○
101.6 × 5.0	68.28	○
110.0 × 5.0	74.22	○
114.3 × 3.0	47.20	○
114.3 × 5.0	77.26	○
120.0 × 5.0	81.29	○
127.0 × 3.0	52.59	○
127.0 × 5.0	86.24	○
130.0 × 5.0	88.36	○
140.0 × 5.0	95.43	○
150.0 × 5.0	102.49	○
152.4 × 3.0	63.36	○
152.4 × 5.0	104.19	○

※ 重量参考 値

\*在庫状況・切断等につきましてはお問合せ下さい。