

アニール銅管(なまし銅管)

JIS 規格 H3300 C1220T O

旧 呼 称 DCuT

特性の概要 冷間引抜き後、焼鈍処理をしているので、調質はO材(なまし材)である。
曲げ加工などがしやすい。

寸 法	P/kg		寸 法	P/kg	
3.0 × 0.5 × 10m	0.35	○	10.0 × 0.8 × 20m	4.16	○
4.0 × 0.5 × 10m	0.49	○	10.0 × 1.0 × 10m	2.54	○
4.0 × 0.8 × 10m	0.72	○	10.0 × 1.0 × 20m	5.09	○
4.0 × 1.0 × 10m	0.85	○	10.0 × 1.0 × 100m	25.45	○
5.0 × 0.8 × 20m	1.90	○	10.0 × 1.0 × 200m	50.89	○
5.0 × 1.0 × 20m	2.26	○	10.0 × 1.2 × 10m	2.99	○
6.0 × 0.8 × 10m	1.18	○	10.0 × 1.2 × 30m	8.96	○
6.0 × 0.8 × 20m	2.35	○	10.0 × 1.2 × 100m	29.86	○
6.0 × 1.0 × 20m	2.83	○	10.0 × 1.5 × 10m	3.60	○
6.0 × 1.2 × 10m	1.63	○	10.0 × 1.5 × 30m	10.81	○
6.4 × 0.8 × 10m	1.25	○	10.0 × 1.5 × 100m	36.05	○
6.4 × 0.8 × 20m	2.50	○	10.0 × 2.0 × 25m	11.31	○
6.4 × 1.0 × 10m	1.50	○	10.0 × 2.0 × 30m	31.57	○
8.0 × 0.8 × 10m	1.63	○	12.0 × 1.0 × 10m	3.11	○
8.0 × 0.8 × 20m	3.26	○	12.0 × 1.0 × 20m	6.22	○
8.0 × 1.0 × 10m	1.98	○	12.0 × 1.0 × 100m	31.10	○
8.0 × 1.0 × 20m	3.96	○	12.0 × 1.2 × 10m	3.66	○
8.0 × 1.0 × 200m	39.58	○	12.0 × 1.2 × 30m	10.99	○
8.0 × 1.2 × 10m	2.31	○	12.0 × 1.2 × 100m	36.64	○
8.0 × 1.2 × 30m	6.92	○	12.0 × 1.5 × 20m	8.91	○
8.0 × 1.5 × 30m	8.27	○	12.0 × 1.5 × 30m	13.36	○
8.0 × 2.0 × 30m	10.18	○	12.0 × 2.0 × 30m	16.96	○
9.52 × 0.8 × 10m	1.97	○	12.7 × 0.8 × 20m	5.38	○
9.5 × 0.8 × 20m	3.94	○	12.7 × 0.8 × 50m	13.46	○
9.5 × 0.8 × 50m	9.84	○	12.7 × 1.0 × 10m	3.31	○
9.5 × 1.0 × 10m	2.40	○	12.7 × 1.0 × 20m	6.62	○
9.5 × 1.0 × 20m	4.81	○	12.7 × 1.0 × 100m	33.08	○
9.5 × 1.0 × 100m	24.03	○	14.0 × 1.0 × 10m	3.68	○
10.0 × 0.8 × 10m	2.08	○	15.0 × 1.0 × 20m	7.92	○

※ 重量参考 値

*在庫状況・切断等につきましてはお問合せ下さい。

アニール銅管(なまし銅管)

寸 法	P/kg	
15.0 × 1.2 × 30m	14.05	○
15.0 × 1.5 × 30m	17.18	○
15.0 × 2.0 × 30m	22.05	○
15.9 × 1.0 × 10m	4.21	○
15.9 × 1.0 × 20m	8.43	○
15.9 × 1.0 × 50m	21.06	○
15.9 × 1.2 × 10m	4.99	○
15.9 × 1.2 × 20m	9.98	○
15.9 × 1.5 × 30m	18.32	○
16.0 × 2.0 × 30m	23.58	○
19.0 × 1.0 × 10m	5.09	○
19.0 × 1.0 × 20m	10.18	○
19.0 × 1.0 × 50m	25.45	○
19.0 × 1.2 × 10m	6.04	○
19.0 × 1.2 × 20m	12.08	○
22.2 × 1.0 × 10m	6.2	○

※ 重量参考 値

*在庫状況・切断等につきましてはお問合せ下さい。