

# SUS303センターレス丸棒

JIS 規格 SUS303

寸法公差=h7

**特性の概要** 被削性、耐熱性向上。自動盤用として最適。

**用途** 機械部品、治工具、シャフト、ボルト、ナット 等

◎当社在庫品 ○取寄せ品

定尺:2000

径	m/kg	公差		径	m/kg	公差	
2	0.024	+0~-0.010	◎	25	3.89	+0~-0.021	◎
4	0.038	+0~-0.012	◎	28	4.88	"	○
3	0.056	+0~-0.010	◎	30	5.60	"	○
3.5	0.076	+0~-0.012	◎	32	6.38	+0~-0.025	○
4	0.099	+0~-0.012	◎	35	7.63	"	○
5	0.156	"	◎	38	8.99	"	○
6	0.224	"	◎	40	9.96	"	○
7	0.305	+0~-0.015	◎	42	11.00	"	○
8	0.399	"	◎	45	12.60	"	○
9	0.504	"	◎	50	15.60	"	○
10	0.623	"	◎				
11	0.753	+0~-0.018	◎				
12	0.897	"	◎				
13	1.05	"	◎				
14	1.22	"	○				
15	1.40	"	◎				
16	1.59	"	◎				
17	1.80	"	◎				
18	2.02	"	◎				
19	2.25	+0~-0.021	◎				
20	2.49	"					
22	3.01	"					
24	3.6	"					

※ 重量参考 値

\*在庫状況・切断等につきましてはお問合せ下さい。