

SUS304センターレス丸棒

JIS 規格 SUS304

寸法公差=h7

特性の概要 オーステナイト系の代表鋼種。ステンレス鋼として最も広く使用される。

用途 一般化学工業設備、食品製造設備 等

◎当社在庫品 ○取寄せ品

定尺:2000

径	m/kg	公差		径	m/kg	公差	
2	0.024	+0~-0.010	○	35	7.63	+0~-0.025	○
2.5	0.038	"	○	38	8.99	"	○
3	0.056	"	○	40	9.96	"	○
3.5	0.076	+0~-0.012	○	42	11.00	"	○
4	0.099	"	○	45	12.60	"	○
4.5	0.125	"	○	50	15.60	"	○
5	0.156	"	◎				
6	0.224	"	◎				
7	0.305	+0~-0.015	○				
8	0.399	"	○				
9	0.504	"	◎				
10	0.623	"	◎				
11	0.753	+0~-0.018	○				
12	0.897	"	◎				
13	1.05	"	○				
14	1.22	"	◎				
15	1.40	"	◎				
16	1.59	"	○				
17	1.80	"	○				
18	2.02	"	◎				
19	2.25	+0~-0.021	○				
20	2.49	"	○				
22	3.01	"	○				
24	3.59	"	○				
25	3.89	"	◎				
26	4.21	"	○				
28	4.88	"	○				
30	5.60	"	◎				
32	6.38	+0~-0.025	○				

※ 重量参考 値

*在庫状況・切断等につきましてはお問合せ下さい。