

# SUS304配管用丸管(TPA)

JIS 規格 SUS304

**特性の概要** オーステナイト系の代表鋼種。ステンレス鋼として最も広く使用される。  
**用途** 一般化学工業設備、食品製造設備 等

寸 法	m/kg	4m	6m	寸 法	m/kg	4m	6m
6 × 1.0	0.125	○		19.0 × 1.0	0.448	○	
8 × 1.0	0.174	○					
10 × 1.0	0.224	○		19.0 × 1.5	0.654	○	
10 × 1.5	0.318	○		19.0 × 2.0	0.847	○	
10 × 2.0	0.399	○		20.0 × 1.5	0.691	○	
10.5 × 1.0	0.237	○		20.0 × 2.0	0.897	○	
10.5 × 1.5	0.336	○		21.7 × 1.2	0.613	○	
10.5 × 2.0	0.423	○		21.7 × 1.5	0.755	○	
12 × 1.0	0.274	○		21.7 × 2.0	0.981	○	○
12 × 1.5	0.392	○		21.7 × 2.5	1.2	○	○
12 × 2.0	0.498	○		21.7 × 3.0	1.4	○	○
12.7 × 1.0	0.291	○		25.0 × 1.5	0.878	○	
12.7 × 1.5	0.418	○		25.0 × 2.0	1.15	○	
12.7 × 2.0	0.533	○		25.4 × 1.5	0.893	○	
				25.4 × 2.0	1.17	○	
13.8 × 1.2	0.377	○		25.4 × 3.0	1.67	○	
13.8 × 1.5	0.46	○		27.2 × 1.5	0.96	○	
13.8 × 2.0	0.588	○		27.2 × 2.0	1.26	○	○
13.8 × 2.2	0.636	○		27.2 × 2.5	1.54	○	○
13.8 × 3.0	0.807	○		27.2 × 3.0	1.81	○	○
16 × 1.0	0.374	○		30.0 × 1.5	1.16	○	
16 × 1.2	0.443	○		30.0 × 2.0	1.39	○	
16 × 1.5	0.542	○		31.8 × 2.0	1.48	○	
16 × 2.0	0.697	○		32.0 × 1.5	1.14	○	
17.3 × 1.2	0.481	○		32.0 × 2.0	1.49	○	
17.3 × 1.5	0.59	○		32.0 × 3.0	2.17	○	
17.3 × 2.0	0.762	○		34.0 × 1.5	1.21	○	
17.3 × 2.5	0.922	○		34.0 × 2.0	1.59	○	○
17.3 × 3.0	1.07	○		34.0 × 2.5	1.96	○	○

※ 重量参考 値

\*在庫状況・切断等につきましてはお問合せ下さい。

## SUS304配管用丸管(TPA)

寸 法	m/kg	4m	6m	寸 法	m/kg	4m	6m
34.0× 3.0	2.32	○	○	76.3× 3.0	5.48	○	○
34.0× 3.5	2.66	○	○	76.3× 3.5	6.35	○	○
34.0× 4.0	2.99	○	○	76.3× 4.0	7.2	○	○
38.0× 1.5	1.36	○		76.3× 5.0	8.88	○	
38.0× 2.0	1.79	○		76.3× 5.2	9.21	○	○
38.0× 3.0	2.62	○		76.3× 7.0	12.1	○	○
42.7× 1.5	1.54	○		89.1× 2.0	4.34	○	○
42.7× 2.0	2.03	○	○	89.1× 3.0	6.43	○	○
42.7× 3.0	2.97	○	○	89.1× 4.0	8.48	○	○
42.7× 3.5	3.42	○	○	89.1× 5.0	10.5	○	
42.7× 4.0	3.86	○	○	89.1× 5.5	11.5	○	○
48.6× 1.5	1.76	○		89.1× 7.6	15.4	○	○
48.6× 2.0	2.32	○	○	101.6× 2.0	4.96	○	○
48.6× 3.0	3.41	○	○	101.6× 3.0	7.37	○	○
48.6× 3.5	3.93	○	○	101.6× 4.0	9.72	○	○
48.6× 4.0	4.44	○	○	101.6× 5.0	12.0	○	
48.6× 5.1	5.53	○	○	101.6× 5.7	13.6	○	○
50.8× 1.5	1.84	○		101.6× 8.1	18.9	○	○
50.8× 2.0	2.43	○		114.3× 2.0	5.59	○	○
50.8× 3.0	3.57	○		114.3× 3.0	8.32	○	○
60.5× 1.5	2.2	○		114.3× 4.0	11.0	○	○
60.5× 2.0	2.91	○	○	114.3× 5.0	13.6	○	○
60.5× 3.0	4.3	○	○	114.3× 6.0	16.2	○	○
60.5× 3.5	4.97	○	○	114.3× 8.6	22.6	○	○
60.5× 4.0	5.63	○	○	139.8× 2.0	6.87	○	○
60.5× 5.0	6.91	○	○	139.8× 3.0	10.2	○	○
60.5× 5.5	7.54	○	○				
76.3× 1.5	2.79	○					
76.3× 2.0	3.7	○	○				

※ 重量参考 値

\*在庫状況・切断等につきましてはお問合せ下さい。

## SUS304配管用丸管(TPA)

寸 法	m/kg	4m	6m	寸 法	m/kg	4m	6m
139.8× 3.5	11.9	○	○	267.4× 4.0	26.2	○	○
139.8× 4.0	13.5	○	○	267.4× 5.0	32.7	○	
139.8× 5.0	16.8	○	○				
139.8× 6.0	20.0	○		267.4× 6.5	42.2	○	○
139.8× 6.6	21.9	○	○	267.4× 9.3	59.8	○	○
139.8× 9.5	30.8	○	○	267.4× 15.1	94.9	○	○
152.4× 3.0	11.2	○		318.5× 3.0	23.6	○	○
165.2× 3.0	12.1	○	○	318.5× 4.0	31.3	○	○
				318.5× 4.5	35.2	○	○
165.2× 3.5	14.1	○	○	318.5× 5.0	39.0	○	
165.2× 4.0	16.1	○	○	318.5× 6.5	50.5	○	○
165.2× 5.0	20.0	○	○	318.5× 10.3	79.1	○	○
165.2× 6.0	23.8	○		318.5× 17.4	131.0	○	○
165.2× 6.5	25.7	○		下記サイズより TPY-S			
165.2× 7.1	28.0	○	○	355.6× 4.0	35.0	○	○
165.2× 11.0	42.3	○	○	355.6× 5.0	43.7	○	○
190.7× 3.0	14.0	○		355.6× 6.0	52.3	○	
190.7× 4.0	18.6	○		355.6× 6.5	56.5	○	
190.7× 6.0	27.6	○		355.6× 8.0	69.3	○	○
216.3× 3.0	15.9	○	○	355.6× 11.1	95.3	○	○
216.3× 4.0	21.2	○	○	355.6× 19.0	159.0	○	
216.3× 5.0	26.3	○		406.4× 4.0	40.1	○	○
				406.4× 4.5	45.1	○	○
216.3× 6.5	34.0	○	○	406.4× 5.0	50.0	○	○
216.3× 8.2	42.5	○	○	406.4× 6.0	59.8	○	○
216.3× 12.7	64.4	○	○	406.4× 6.5	64.7	○	
241.8× 3.0	17.8	○		406.4× 8.0	79.4	○	○
				406.4× 12.7	125.0	○	○
267.4× 3.0	19.8	○	○	457.2× 4.0	45.2	○	
267.4× 3.5	23.0	○	○	457.2× 4.5	50.7	○	

※ 重量参考 値

\*在庫状況・切断等につきましてはお問合せ下さい。

## SUS304配管用丸管(TPY-S)

寸 法	m/kg	4m	6m
457.2 × 5.0	56.3	○	○
457.2 × 6.0	67.4	○	
457.2 × 8.0	89.5	○	○
457.2 × 14.3	158.0	○	
508.0 × 4.0	50.2	○	
508.0 × 5.0	62.6	○	○
508.0 × 5.5	68.8	○	
508.0 × 6.0	75.0	○	○
508.0 × 9.5	118.0	○	○
508.0 × 15.1	185.0	○	
558.8 × 5.0	69.0	○	
558.8 × 6.0	82.6	○	
558.8 × 5.5	75.8	○	
558.8 × 9.5	130.0	○	
558.8 × 15.9	215.0	○	
609.6 × 5.0	75.3	○	
609.6 × 5.5	82.8	○	
609.6 × 6.0	90.2	○	
609.6 × 6.5	97.7	○	○
609.6 × 9.5	142.0	○	○
609.6 × 17.5	258.0	○	
660.4 × 6.0	97.8	○	
660.4 × 8.0	130.0	○	
660.4 × 12.7	205.0	○	
711.2 × 6.0	105.0	○	
711.2 × 8.0	140.0	○	
711.2 × 12.7	221.0	○	

\*在庫状況・切断等につきましてはお問せください。

※ 重量参考値