

SUS304配管用継目無管(TPS)

JIS 規格 SUS304

特性の概要 オーステナイト系の代表鋼種。ステンレス鋼として最も広く使用される。
用途 一般化学工業設備、食品製造設備 等

| 寸 法 | P/重量 | 4m | 6m | 寸 法 | P/重量 | 4m | 6m |
|--------------|------|----|----|--------------|------|----|----|
| 4.0 x 0.5 | 0.18 | ○ | | 8.0 x 2.0 | 1.20 | ○ | |
| 4.0 x 1.0 | 0.30 | ○ | | 9.0 x 0.5 | 0.40 | ○ | |
| 5.0 x .0.5 | 0.22 | ○ | | 9.0 x 1.0 | 0.80 | ○ | |
| 5.0 x 1.0 | 0.40 | ○ | | 9.0 x 1.5 | 1.12 | ○ | |
| 5.0 x 1.5 | 0.52 | ○ | | 9.0 x 2.0 | 1.40 | ○ | |
| 6.0 x .0.5 | 0.28 | ○ | | 9.53 x 0.889 | 0.76 | ○ | |
| 6.0 x 0.8 | 0.42 | ○ | | 9.53 x 0.89 | 0.77 | ○ | |
| 6.0 x 1.0 | 0.50 | ○ | | 9.53 x 1.0 | 0.85 | ○ | |
| 6.0 x 1.2 | 0.57 | ○ | | 9.53 x 1.2 | 1.00 | ○ | |
| 6.0 x 1.5 | 0.67 | ○ | | 9.53 x 1.24 | 1.02 | ○ | |
| 6.0 x 2.0 | 0.80 | ○ | | 9.53 x 1.5 | 1.20 | ○ | |
| 6.35 x 0.5 | 0.29 | ○ | | 9.53 x 1.65 | 1.30 | ○ | |
| 6.35 x 0.889 | 0.48 | ○ | | 9.53 x 2.0 | 1.50 | ○ | |
| 6.35 x 1.0 | 0.53 | ○ | | 10.0 x 0.5 | 0.47 | ○ | |
| 6.35 x 1.2 | 0.62 | ○ | | 10.0 x 0.8 | 0.73 | ○ | |
| 6.35 x 1.5 | 0.72 | ○ | | 10.0 x 1.0 | 0.90 | ○ | |
| 7.0 x 0.5 | 0.32 | ○ | | 10.0 x 1.2 | 1.05 | ○ | |
| 7.0 x 1.0 | 0.60 | ○ | | 10.0 x 1.5 | 1.27 | ○ | |
| 7.0 x 1.5 | 0.82 | ○ | | 10.0 x 2.0 | 1.60 | ○ | |
| 7.0 x 2.0 | 1.00 | ○ | | 10.0 x 2.5 | 1.87 | ○ | |
| 8.0 x 0.5 | 0.37 | ○ | | 10.0 x 3.0 | 2.09 | ○ | |
| 8.0 x 0.8 | 0.57 | ○ | | 10.5 x 1.0 | 0.95 | ○ | |
| 8.0 x 1.0 | 0.70 | ○ | | 10.5 x 1.2 | 1.11 | ○ | |
| 8.0 x 1.2 | 0.81 | ○ | | 10.5 x 1.5 | 1.34 | ○ | |
| 8.0 x 1.5 | 0.97 | ○ | | 10.5 x 1.7 | 1.49 | ○ | |
| | | | | 10.5 x 2.0 | 1.70 | ○ | |

*在庫状況・切断等につきましてはお問合せ下さい。

※ 重量参考 値

SUS304配管用丸管(TPS)

| 寸 法 | P/重量 | 4m | 6m | 寸 法 | P/重量 | 4m | 6m |
|-------------|------|----|----|--------------|------|----|----|
| 10.5 x 2.4 | 1.94 | ○ | | 14.0 x 1.0 | 1.3 | ○ | |
| 12.0 x 0.5 | 0.57 | ○ | | 14.0 x 1.5 | 1.87 | ○ | |
| 12.0 x 1.0 | 1.10 | ○ | | 14.0 x 2.0 | 2.39 | ○ | |
| 12.0 x 1.2 | 1.29 | ○ | | 14.0 x 3.0 | 3.29 | ○ | |
| 12.0 x 1.5 | 1.57 | ○ | | 15.0 x 1.0 | 1.40 | ○ | |
| 12.0 x 2.0 | 1.99 | ○ | | 15.0 x 1.2 | 1.65 | ○ | |
| 12.0 x 2.5 | 2.37 | ○ | | 15.0 x 1.5 | 2.02 | ○ | |
| 12.0 x 3.0 | 2.69 | ○ | | 15.0 x 2.0 | 2.59 | ○ | |
| 12.7 x 0.89 | 1.05 | ○ | | 15.0 x 2.5 | 3.11 | ○ | |
| 12.7 x 1.0 | 1.16 | ○ | | 15.0 x 3.0 | 3.59 | ○ | |
| 12.7 x 1.2 | 1.38 | ○ | | 15.88 x 0.89 | 1.33 | ○ | |
| 12.7 x 1.5 | 1.67 | ○ | | 16.0 x 1.0 | 1.50 | ○ | |
| 12.7 x 1.65 | 1.82 | ○ | | 16.0 x 1.2 | 1.77 | ○ | |
| 12.7 x 2.0 | 2.13 | ○ | | 16.0 x 1.5 | 2.17 | ○ | |
| 13.0 x 0.5 | 0.62 | ○ | | 16.0 x 2.0 | 2.79 | ○ | |
| 13.0 x 1.0 | 1.20 | ○ | | 16.0 x 3.0 | 3.89 | ○ | |
| 13.0 x 1.5 | 1.72 | ○ | | 16.0 x 4.0 | 4.80 | ○ | |
| 13.0 x 2.0 | 2.19 | ○ | | 17.3 x 1.2 | 1.92 | ○ | |
| 13.0 x 3.0 | 2.99 | ○ | | 17.3 x 1.65 | 2.57 | ○ | |
| 13.8 x 1.2 | 1.51 | ○ | | 17.3 x 2.0 | 3.05 | ○ | |
| 13.8 x 1.65 | 2.00 | ○ | | 17.3 x 2.3 | 3.44 | ○ | |
| 13.8 x 2.0 | 2.35 | ○ | | 17.3 x 3.2 | 4.48 | ○ | |
| 13.8 x 2.2 | 2.54 | ○ | | 17.3 x 4.0 | 5.32 | ○ | |
| 13.8 x 3.0 | 3.23 | ○ | | 18.0 x 1.0 | 1.69 | ○ | |
| 13.8 x 4.0 | 3.90 | ○ | | 18.0 x 1.5 | 2.47 | ○ | |

*在庫状況・切断等につきましてはお問合せ下さい。

※ 重量参考 値

SUS304配管用丸管(TPS)

| 寸 法 | P/重量 | 4m | 6m | 寸 法 | P/重量 | 4m | 6m |
|-------------|------|----|----|-------------|------|----|----|
| 18.0 x 2.0 | 3.19 | ○ | | 22.0 x 1.0 | 2.09 | ○ | |
| 18.0 x 3.0 | 4.48 | ○ | | 22.0 x 1.5 | 3.06 | ○ | |
| 18.0 x 4.0 | 5.56 | ○ | | 22.0 x 2.0 | 3.98 | ○ | |
| 19.0 x 1.0 | 1.79 | ○ | | 22.0 x 3.0 | 5.68 | ○ | |
| 19.0 x 1.2 | 2.13 | ○ | | 25.0 x 1.0 | 2.39 | ○ | |
| 19.0 x 1.5 | 2.62 | ○ | | 25.0 x 1.5 | 3.51 | ○ | |
| 19.0 x 2.0 | 3.39 | ○ | | 25.0 x 2.0 | 4.60 | ○ | |
| 19.0 x 3.0 | 4.80 | ○ | | 22.0 x 1.5 | 3.06 | ○ | |
| 19.0 x 4.0 | 5.96 | ○ | | 22.0 x 2.0 | 3.98 | ○ | |
| 19.0 x 5.0 | 6.96 | ○ | | 22.0 x 3.0 | 5.68 | ○ | |
| 20.0 x 1.0 | 1.89 | ○ | | 25.0 x 1.0 | 2.39 | ○ | |
| 20.0 x 1.2 | 2.25 | ○ | | 25.0 x 1.5 | 3.51 | ○ | |
| 20.0 x 1.5 | 2.76 | ○ | | 25.0 x 2.0 | 4.60 | ○ | |
| 20.0 x 2.0 | 3.59 | ○ | | 25.0 x 3.0 | 6.56 | ○ | |
| 20.0 x 3.0 | 5.08 | ○ | | 25.0 x 3.5 | 7.48 | ○ | |
| 20.0 x 4.0 | 6.36 | ○ | | 25.0 x 4.0 | 8.36 | ○ | |
| 20.0 x 5.0 | 7.48 | ○ | | 25.0 x 5.0 | 9.96 | ○ | |
| 21.7 x 1.2 | 2.45 | ○ | | 25.4 x 1.0 | 2.43 | ○ | |
| 21.7 x 1.65 | 3.30 | ○ | | 25.4 x 1.2 | 2.89 | ○ | |
| 21.7 x 2.1 | 4.12 | ○ | | 25.4 x 1.5 | 3.57 | ○ | |
| 21.7 x 2.5 | 4.80 | ○ | | 25.4 x 2.0 | 4.68 | ○ | |
| 21.7 x 2.8 | 5.28 | ○ | | 25.4 x 3.0 | 6.68 | ○ | |
| 21.7 x 3.7 | 6.64 | ○ | | 25.4 x 4.0 | 8.52 | ○ | |
| 21.7 x 4.7 | 7.96 | ○ | | 27.2 x 1.65 | 4.20 | ○ | |
| 21.7 x 7.5 | 10.6 | ○ | | 27.2 x 2.1 | 5.24 | ○ | |

*在庫状況・切断等につきましてはお問合せ下さい。

※ 重量参考 値

SUS304配管用丸管(TPS)

| 寸 法 | P/重量 | 4m | 6m | 寸 法 | P/重量 | 4m | 6m |
|-------------|-------|----|----|-------------|-------|----|----|
| 27.2 x 2.5 | 6.16 | ○ | | 34.0 x 3.0 | 9.28 | ○ | |
| 27.2 x 2.9 | 7.04 | ○ | | 34.0 x 3.4 | 10.36 | ○ | |
| 27.2 x 3.9 | 9.04 | ○ | | 34.0 x 4.5 | 13.24 | ○ | |
| 27.2 x 5.5 | 11.88 | ○ | | 34.0 x 6.4 | 17.6 | ○ | |
| 27.2 x 7.8 | 15.08 | ○ | | 34.0 x 9.1 | 22.56 | ○ | |
| 28.0 x 2.0 | 5.20 | ○ | | 36.0 x 2.0 | 6.76 | ○ | |
| 28.0 x 3.0 | 7.48 | ○ | | 36.0 x 3.0 | 9.88 | ○ | |
| 28.0 x 4.0 | 9.56 | ○ | | 36.0 x 5.0 | 15.44 | ○ | |
| 30.0 x 1.5 | 4.24 | ○ | | 42.7 x 1.65 | 6.76 | ○ | |
| 30.0 x 2.0 | 5.56 | ○ | | 42.7 x 2.0 | 8.12 | ○ | |
| 30.0 x 2.5 | 6.84 | ○ | | 42.7 x 2.8 | 11.12 | ○ | |
| 30.0 x 3.0 | 8.08 | ○ | | 42.7 x 3.0 | 11.88 | ○ | |
| 30.0 x 4.0 | 10.36 | ○ | | 42.7 x 3.6 | 14.04 | ○ | |
| 30.0 x 5.0 | 12.44 | ○ | | 42.7 x 4.9 | 18.44 | ○ | |
| 32.0 x 1.5 | 4.56 | ○ | | 42.7 x 6.4 | 23.16 | ○ | |
| 32.0 x 2.0 | 5.96 | ○ | | 42.7 x 8.0 | 27.68 | ○ | |
| 32.0 x 2.5 | 7.36 | ○ | | 42.7 x 9.5 | 31.44 | ○ | |
| 32.0 x 3.0 | 8.68 | ○ | | 42.7 x 10.0 | 32.6 | ○ | |
| 32.0 x 4.0 | 11.16 | ○ | | 45.0 x 3.0 | 12.56 | ○ | |
| 32.0 x 5.0 | 13.44 | ○ | | 48.6 x 1.65 | 7.72 | ○ | |
| 32.0 x 6.0 | 15.56 | ○ | | 48.6 x 2.0 | 9.28 | ○ | |
| 32.0 x 8.0 | 19.12 | ○ | | 48.6 x 2.8 | 12.76 | ○ | |
| 34.0 x 1.65 | 5.32 | ○ | | 48.6 x 3.0 | 13.64 | ○ | |
| 34.0 x 2.0 | 6.36 | ○ | | 48.6 x 3.7 | 16.56 | ○ | |
| 34.0 x 2.8 | 8.72 | ○ | | | | | |

*在庫状況・切断等につきましてはお問合せ下さい。

※ 重量参考 値

SUS304配管用丸管(TPS)

| 寸 法 | P/重量 | 4m | 6m | 寸 法 | P/重量 | 4m | 6m |
|-------------|-------|----|----|--------------|-------|----|----|
| 48.6 x 5.1 | 22.12 | ○ | | 76.3x 9.5 | 63.2 | ○ | |
| 48.6 x 7.1 | 29.36 | ○ | | 76.3 x 13.5 | 84.4 | ○ | |
| 48.6 x 8.7 | 34.6 | ○ | | 76.3 x 14.0 | 86.8 | ○ | |
| 48.6 x 10.2 | 39.04 | ○ | | 76.3 x 15.0 | 91.6 | ○ | |
| 60.5 x 1.65 | 9.68 | ○ | | 89.1 x 2.1 | 18.2 | ○ | |
| 60.5 x 2.0 | 11.64 | ○ | | 89.1 x 3.0 | 25.72 | ○ | |
| 60.5 x 2.8 | 16.08 | ○ | | 89.1 x 4.0 | 33.92 | ○ | |
| 60.5 x 3.0 | 17.2 | ○ | | 89.1 x 5.5 | 46.0 | ○ | |
| 60.5 x 3.5 | 19.88 | ○ | | 89.1 x 7.6 | 61.6 | ○ | |
| 60.5 x 3.9 | 22.0 | ○ | | 89.1 x 11.1 | 86.4 | ○ | |
| 60.5 x 4.9 | 27.16 | ○ | | 101.6 x 2.1 | 20.8 | ○ | |
| 60.5 x 5.5 | 30.16 | ○ | | 101.6 x 3.0 | 29.48 | ○ | |
| 60.5 x 6.0 | 32.6 | ○ | | 101.6 x 4.0 | 38.88 | ○ | |
| 60.5 x 8.7 | 44.8 | ○ | | 101.6 x 5.7 | 54.4 | ○ | |
| 60.5 x 10.0 | 50.4 | ○ | | 101.6 x 8.1 | 75.6 | ○ | |
| 60.5 x 11.1 | 54.8 | ○ | | 101.6 x 12.7 | 112.4 | ○ | |
| 60.5 x 15.0 | 68.0 | ○ | | 101.6 x 15.0 | 129.6 | ○ | |
| 65.0 x 2.0 | 12.56 | ○ | | 114.3 x 2.1 | 23.48 | ○ | |
| 70.0 x 7.0 | 44.0 | ○ | | 114.3 x 3.0 | 33.28 | ○ | |
| 76.3 x 2.1 | 15.52 | ○ | | 114.3 x 4.0 | 44.0 | ○ | |
| 76.3 x 3.0 | 21.92 | ○ | | 114.3 x 6.0 | 64.8 | ○ | |
| 76.3 x 3.5 | 25.4 | ○ | | 114.3 x 8.6 | 90.4 | ○ | |
| 76.3 x 4.0 | 28.8 | ○ | | 114.3 x 11.1 | 114.0 | ○ | |
| 76.3 x 5.2 | 36.84 | ○ | | 114.3 x 13.5 | 135.6 | ○ | |
| 76.3 x 7.0 | 48.4 | ○ | | 114.3 x 17.1 | 165.6 | ○ | |

*在庫状況・切断等につきましてはお問合せ下さい。

※ 重量参考 値

SUS304配管用丸管(TPS)

| 寸 法 | P/重量 | 4m | 6m | 寸 法 | P/重量 | 4m | 6m |
|--------------|-------|----|----|--------------|-------|----|----|
| 139.8 x 2.8 | 38.24 | ○ | | 267.4 x 15.1 | 379.6 | ○ | |
| 139.8 x 3.4 | 46.4 | ○ | | 267.4 x 21.4 | 524.0 | ○ | |
| 139.8 x 5.0 | 67.2 | ○ | | 267.4 x 28.6 | 680.0 | ○ | |
| 139.8 x 6.6 | 87.6 | ○ | | 318.5 x 4.0 | 125.2 | ○ | |
| 139.8 x 9.5 | 123.2 | ○ | | 318.5 x 4.5 | 140.8 | ○ | |
| 139.8 x 12.7 | 160.8 | ○ | | 318.5 x 6.5 | 202.0 | ○ | |
| 139.8 x 15.9 | 196.4 | ○ | | 318.5 x 10.3 | 316.4 | ○ | |
| 165.2 x 2.8 | 45.2 | ○ | | 318.5 x 17.4 | 524.0 | ○ | |
| 165.2 x 3.4 | 54.8 | ○ | | 318.5 x 25.4 | 740.0 | ○ | |
| 165.2 x 5.0 | 80.0 | ○ | | 318.5 x 33.3 | 948.0 | ○ | |
| 165.2 x 7.1 | 112.0 | ○ | | 355.6 x 11.1 | 381.2 | ○ | |
| 165.2 x 11.0 | 169.2 | ○ | | 406.4 x 12.7 | 500.0 | ○ | |
| 165.2 x 14.3 | 215.2 | ○ | | 406.4 x 21.4 | 820.0 | ○ | |
| 165.2 x 18.2 | 266.4 | ○ | | | | | |
| 216.3 x 2.8 | 59.6 | ○ | | | | | |
| 216.3 x 4.0 | 84.8 | ○ | | | | | |
| 216.3 x 6.5 | 136.0 | ○ | | | | | |
| 216.3 x 8.2 | 170.0 | ○ | | | | | |
| 216.3 x 12.7 | 257.6 | ○ | | | | | |
| 216.3 x 18.2 | 359.2 | ○ | | | | | |
| 216.3 x 23.0 | 444.0 | ○ | | | | | |
| 267.4 x 3.4 | 89.6 | ○ | | | | | |
| 267.4 x 4.0 | 104.8 | ○ | | | | | |
| 267.4 x 6.5 | 168.8 | ○ | | | | | |
| 267.4 x 9.3 | 239.2 | ○ | | | | | |

*在庫状況・切断等につきましてはお問合せ下さい。

※ 重量参考 値

